


R540 RLTD TRUCK 2D

2D TECHNOLOGY ELECTRONIC BALANCER with MICROPROCESSOR

AUTO STOP ON TOP / AUTO LOCK

Automatic stop of the wheel in the external unbalanced position.



LARGE DIGITAL DISPLAY
Integrated keyboard

AUTOMATIC BALANCING MODE

Versatile machine designed for easy, fast and accurate balancing of motorcycle, car and commercial wheels.

Microprocessor controlled with self-calibration and self-diagnostics.

Specific balancing programs for static, dynamic and ALU wheels. One single spin with low rotation speed provides all the values. Readout of out of balance values and the related position on the wheel. Wheel diameter and width in inches or millimeters. Unbalance readout in grams or ounces.



**STANDARD
AIR TIRE LIFT**
441 Lbs. capacity

STANDARD ACCESSORIES



GAR 111
Passenger tire cone kit
1.75" - 4" (44-104 mm)




CALIBRATION KIT



GAR 344
Quick lock

AIR BRAKE

An electro-pneumatic brake keeps the wheel in the unbalance position.



Wheel diameter: 10" - 30"
Tire width: 1.5" - 22"
Maximum tire diameter: 51"

R540 RTLD services:



Optional equipment may be required

DIMENSIONS:

HEIGHT: 40"
WIDTH: 69.5"
DEPTH: 26.25"



GAR 112
Light truck cone
3.75" - 5"
(95-124 mm)



GAR 113
Light truck cone
4.65" - 6.8"
(118-174 mm)



GAR 122
Truck spacer



GAR124

Spacer
May be used with GAR112 and the #8,9,10,11 collets

GAR 114 202/221/281
2 Cones for trucks
7.9" - 8.7" - 11"

TECHNICAL DATA	R540
Maximum assembly weight	441 lbs. (200kg)
Read out accuracy	10 g 1 g
Rotation speed (rpm)	100 80
Power supply	110v / 60 Hz / 1Ø

OPTIONAL ACCESSORIES / R544 PLUS / R540 RLTD

CAMION / TRUCK / LKW APPLICATION

GAR 171 three finger adapter
(3X170, 186, 205, 222, 245)

GAR 172 four finger adapter
(4X275, 285) 202-221-281

GAR 173 five finger adapter
(5X225, 286, 335)



**SHOWN:
GAR 172**
Four finger adapter



HW700E400020
Truck centering disc
Fits 219.9mm / 8.65" and 220.8mm / 8.69"
Requires GAR173 and/or GAR172 for use



GAR 266T
WIDTH SENSOR
3D wheel tire sensor caliper for automatic measure of rim width
Standard with R544 PLUS balancer
Can be added to older R544 Series models
NOT available for R540 balancer