



Counteract
OFF ROAD
ATV & UTV **Tire Balancing**

Note: Due to the nature and uses of ATV/UTV tires, Counteract cannot guarantee a 100% balance. The use of this product in ATV/UTV applications is for a smoother, less fatiguing drive with an 80% decrease in vibration. Counteract is however the best means of providing balance to these applications.

ATV Tire Size

Wheel Width	Ounces Required
Less than 10" width	2oz
10" – 12" width	3oz
Larger than 12" width	4oz

ATV/UTV Tire Sizes

Tire Height	Ounces Required
23" – 29"	4oz
30" – 33"	6oz
33" – 37"	8oz
37" – Up	10oz

Kits Available:

All kits include Counteract Balancing Beads, Valve Cores, Valve Caps, Valve Core Remover, Injection Bottle and Tube.

- Kit H = 4 x 2oz
- Kit I = 2 x 2oz + 2 x 3oz
- Kit J = 4 x 3oz
- Kit K = 4 x 4oz
- Kit L = 4 x 6oz
- Kit M = 4 x 8oz
- Kit N = 4 x 10oz

Disclaimer

Counteract does not accept any responsibility for use in Sand Paddle tires. These tires are not designed to be driven on road, and therefore cannot be balanced.



Example
Height x Width x Wheel Diameter

20"x11"x8