


CL10V3 - 2-POST

MODEL NUMBER	CL10V3	CL10V3-DPC-QC	CL10-XP9	CL10-XP9-DPC-QC
Description	Versymmetric®	Versymmetric® w/ DPC & QuickCycle™	10K w/ XP9	10K with XP9, DPC & QuickCycle™
Lifting Capacity	10,000 lbs.		9,000 lbs.	
Lift Configuration	Versymmetric®, 3-Stage Front & Rear		Drive-on Express Pad	
Rise Height	74 1/8"		70"	
Height of Columns	Standard 11' 8" or 11' 2" with 2' or 3' extensions			
Max. Extended Cylinder Height	11' 11"			
Adjustable Width Overall	11' 6 1/2" - 11' 11"			
Drive Thru Clearance	8' 4" / 8' 8 1/2"		7' 7" / 7' 11 1/2"	
Floor to Overhead Switch	Standard 11' 2 1/2" or 10' 8 1/2" with 2' or 3' extensions			
Front Arm Reach	Min. 20" Max. 42"		NA	
Rear Arm Reach	Min. 37 5/8" Max. 60"		NA	
Screw Pad Height	Min. 3 7/8" Max. 6 1/8"		NA	
Inside Columns	Min. 9' 2" Max. 9' 6 1/2"		NA	
Low Lock Height	12" Net Rise			
Platform Length	NA		58" / 66 1/2" / 75"	
Standard Motor/Voltage	2HP, 208v-230v, 60Hz, 1Ph	3HP, 208v-230v, 60Hz, 1Ph	2HP, 208v-230v, 60Hz, 1Ph	3HP, 208v-230v, 60Hz, 1Ph
Rise Time	38s	24s	38s	24s
Max. Load per Arm	2,500 lb.		NA	
Required Ceiling Height	Standard 12'			
ALI® Certified	<input checked="" type="checkbox"/>			
Available Colors				

CL12A | CL12A-LC - 2-POST

MODEL NUMBER	CL12A-LC	CL12A-LC-DPC-QC	CL12A	CL12A-1	CL12A-2	CL12A-DPC-QC
Description	Low-Ceiling	Low-Ceiling w/ DPC and QuickCycle™	Standard	Standard with 1' Height Extensions	Standard with 2' Height Extensions	Standard w/ DPC and QuickCycle™
Lifting Capacity	12,000 lbs.					
Lift Configuration	Symmetric					
Arm Configuration	3-Stage Front & Rear					
Rise Height	80 3/4"		84 3/4"			
Overall Height	11' 11"		13' 8" or 13' 2"	14' 8" or 14' 2"	15' 8" or 15' 2"	13' 8" or 13' 2"
Overall Width	Standard - 11' 10"					
	+6" - 12' 4"					
	+12" - 12' 10"					
Drive Thru Clearance	Standard - 8' 7 1/2"					
	+6" - 9' 1 1/2"					
	+12" - 9' 7 1/2"					
Floor to Overhead Switch	11' 4 1/2"		13' 2" or 12' 8"	14' 2" or 13' 8"	15' 2" or 14' 8"	13' 2" or 12' 8"
Arm Reach	Min. 27 1/2" Max. 59"					
Screw Pad Height	Min. 5" Max. 12 5/8" (includes 6" stack adapter)					
Standard Motor/Voltage	2HP, 208v-230v, 60Hz, 1Ph	3HP, 208v-230v, 60Hz, 1Ph	2HP, 208v-230v, 60Hz, 1Ph			3HP, 208v-230v, 60Hz, 1Ph
Rise Time	60s	38s	63s			40s
Min. Ceiling Height	12'		13' 9" or 13' 3"	14' 9" or 14' 3"	15' 9" or 15' 3"	13' 9" or 13' 3"
ALI® Certified	<input checked="" type="checkbox"/>					
Available Colors	