



Counteract Balancing Beads Inc.
 8-70 Watson Parkway South
 Guelph, Ontario – 1.800.572.8952

FRONT Tire Width	Ounces Required
80mm-120mm	1oz
130mm-240mm	2oz
240mm - Up	3oz

REAR Tire Width	Ounces Required
130mm-240mm	2oz
250mm-360mm	3oz
195-205 Car Tire on Rear	3oz

Scoters	Ounces Required
10" Rim Diameter	1oz
12" & Up Rim Diameter	2oz

Dual Purpose, Dirt Bike w/ Rim Lock	Ounces Required
Front 80mm-120mm	2oz
Rear 130mm-230mm	3oz

Tube Type Tire, Wire Spoke Rim	Ounces Required
80mm-120mm	2oz
130mm-240mm	2oz

Harley-Dunlop Tire Size Conversion (MT90B16)

MT, MH, MJ etc = Tire Width, 90 = Tire Profile, B = Rim Diameter

MH = 80mm Width	MR = 120mm Width
MJ = 90mm Width	MT = 130mm Width
MM = 100mm Width	MU = 140mm Width
MN or MP = 110mm Width	MV = 150mm Width

PLEASE NOTE EXCEPTIONS BELOW

- Super Sport bikes can experience a vibration at high triple digit speeds because too much product was added. Please start with 1/2oz in the front tire, regular recommended amount in the rear.

(ZX1000, CBR1000RR, CBR600RR, ZX600R, R1, R6, RC8, etc)



EXAMPLE:

WIDTH / ASPECT RATIO x RIM DIAMETER

110/90x19