

#### ENGINEERED TO PERFORM. BUILT TO LAST.

Reliable lift systems for independent repair shops, car dealerships, bodyshops, home enthusiasts, and heavy-duty truck facilities.

# DP15 PRC

**HEAVY DUTY TWO POST LIFT** 

15,000 lbs. Capacity



## **FEATURES:**

Symmetrical column design

Standard with 3-stage front and rear arms for a greater range of vehicle options

Three height configuration models for most ceiling heights

Top mounted direct pull technology

- Cylinder rod concealed inside carriage
- Overhead cable equalization
- Single point lock release
- Spring operated arm restraints
- Includes adapter storage
- Durable powder-coated finish

SPECIFICATIONS BL=Blue Lift / RD= Red Lift

THREE OVERALL HEIGHT OPTIONS / MODELS

DP15PN000BL / RD 154-3/4" (3930mm) Low Ceiling DP15PN001BL / RD 175" (4445mm) Standard Extension

DP15PN002BL / RD 199" (5054mm) Extended Height

Capacity 15,000 lbs. (6804kg) Minimum Rise 73-1/4" (1860mm)

147-1/4" (3735mm) Low Ceiling

191-1/4" (48514mm) Extended Height

Height to Shut-Off 167-1/4" (4248mm) Standard Extension

Max. Rise with 10" (254mm) 83-1/4" (2120mm)

Overall Floor Width 154-3/8" (3921mm) Width Inside Columns 119-5/8" (3038mm)

Arm Reach (Min/Max) 30"/61" (762mm/1549mm) Threaded Adapter Height 5-1/2" to 7-1/2" (139mm)

Drive Through Clearance 108-1/4" (2750mm)

Max. Adapter Height 15-1/2" (393mm) with 10" Extension

Motor/Phase 1ph/2HP

Voltage/Amps 208V/230V, 17 amps

DP15PN002BL / RD 200" (5080mm) Extended Height

Adapter Extensions

ALI certified

# **HEAVY DUTY 3-STAGE ARM DESIGN**

The DP15 Pro's industry leading 30" arm retraction creates the needed clearance to swing arms between tires of shorter wheelbase vehicles.\*

- 3-stage arms easily extend and retract from 61" to 30"
- 5 1/2" minimum adapter height from floor
- \* For 15,000 pound capacity lifts and above



DP15PN002RI

Extended Height Lift

**INCLUDES LOW-PROFILE THREADED ADAPTER PADS** AND (4 EACH) 5" and 10" ADAPTER EXTENSIONS PROVIDING ADDITIONAL VEHICLE REACH



996 Industrial Drive Madison, IN 47250

Phone: 800.423.1722 Fax: 812.273.7329



### www.forwardlift.com 📑 📵 🔰 🔼



#### MINIMUM REQUIRED CEILING HEIGHT DP15PN000BL / RD 155-3/4" (3956mm) Low Ceiling DP15PN001BL / RD 176" (4470mm) Standard Extension

Specifications subject to change without notice or liability Lift colors are available in blue (BL) and red (RD)