



ENGINEERED TO PERFORM. BUILT TO LAST.

Reliable lift systems for independent repair shops, car dealerships, bodyshops, home enthusiasts, and heavy-duty truck facilities.

**Heavy Duty Top Mounted,
Direct-Pull Lifting
Technology**

DP18

HEAVY DUTY TWO POST LIFT
18,000 lbs. Capacity



DP18N002BL

FEATURES:

Symmetrical column design

2-stage front and rear arms

Four height configuration models for most ceiling heights

Adjustable width options

- Cylinder rod concealed inside carriage
- Overhead cable equalization
- Single point lock release
- Spring operated arm restraints
- Includes adapter storage bracket
- Durable powder-coated finish
- ALI certified

**INCLUDES LOW-PROFILE THREADED
ADAPTER PADS AND (4 each) ADAPTER
EXTENSIONS AT 5" and 10"**



LOW-PROFILE ARM DESIGN

- Arms feature a low, 5 1/2" minimum adapter engagement height
- Two-stage with heavy-duty reinforced gusseting
- Easily extended and retracted (61" to 38")



996 Industrial Drive
Madison, IN 47250

Phone: 800.423.1722
Fax: 812.273.7329



www.forwardlift.com



Lit# Forward DP18 CUTSHEET.2021.06 ©2021 Vehicle Service Group™ All rights reserved.

Unless otherwise indicated, Forward Lift, Vehicle Service Group™, Dover and all other trademarks are property of Dover Corporation and its affiliates. Printed in the U.S.A.

| SPECIFICATIONS | DP18N000BL/RD* |
|--|---|
| Capacity | 15,000 lbs. (6803kg) 18,000 lbs. (8164kg) |
| Maximum Rise with 10" Adapter Extensions | 83" (2120mm) |
| Overall Height | DP18N000 154-3/4" (3930mm) DP18N001 175" (4445mm) DP18N002 199" (5054mm) |
| Height to Shut-Off | 147-1/4" (3735mm) |
| Overall Floor Width | 154-3/8" (3921mm) |
| Width Inside Columns | 119-5/8" (3038mm) |
| Drive Through Clearance | 108-1/4" (2750mm) |
| Arm Reach (Min/Max) | 38" / 61" (965mm/1549mm) |
| Min. Adapter Height | 5-1/2" (139mm) |
| Max. Adapter Height with 10" Extension | 15-1/2" (393mm) |
| Voltage/Amps | 208V/230V, 17 amps |
| Motor/Phase | 1ph/2HP |
| Ceiling Height Required | 155-3/4" (3956mm) |

*Lifts available in blue and red
Specifications subject to change without notice or liability.