



REMA TIP TOP Group of Companies



EV Tire Adhesive Removal Kit

Allows technicians to quickly and easily remove the adhesive that holds the sound insulating foam in place on EV tires. To reach the inner liner and perform a proper tire repair, the adhesive inside the tire must first be removed. The EV Adhesive Removal Kit significantly reduces adhesive removal time from 20 minutes to 5 minutes, without introducing harmful chemicals, solvents, or unrecognized methods to the repair process.

KIT CONTENTS:

- 2 x 3" Roloc Disc
- 1 x Quick Change Adapter
- 1 x 2" Holder

Recommended Speed: 2500-2700 RPM

| Part # | Description | Box/Qty |
|--------|--|---------|
| 71524 | EV Tire Adhesive Removal Kit 2 x 3" Roloc Disc 1 x Quick Change Adapter [2,500 - 2,700 RPM] 1 x 2" Holder | 1 |
| 71525 | Replacement Rolocs for EV Adhesive Removal 2 x Rolocs [2,500 - 2,700 RPM] | 1 |



Scan for
instructional video

Please note: These items are not included in the kit but are recommended for a complete and safe repair of EV tires.

| Part # | Description | Diameter (inch) | Diameter (mm) | Box/Qty |
|-----------|---|-----------------|---------------|---------|
| CC-6 | Carbide Cutter, pointed | ¼ | 6 | 10 |
| 6068 | QR Adapter, ¼" shank, for use with CC-6 & 5950722 | | | 1 |
| 6014 | Brass Cleaning Brush | | | 10 |
| WSW-BRUSH | Brass Bristle Brush - Plastic, Long Handle | | | 1 |
| 5950722 | Wire Brush | 2⅜ | 55 | 1 |

| Part # | Description | Diameter (inch) | Width (inch) | Bore (inch) | SSG | Grit | Box/Qty |
|--------|----------------------|-----------------|--------------|-------------|-----|------|---------|
| RH-109 | Flared contour wheel | 2½ | 2⅞ | ⅜ | 230 | 36 | 1 |

| Part # | Description | Diameter (inch) | Bore (inch) | Box/Qty |
|--------|-------------|-----------------|-------------|---------|
| RH-152 | Polyplug | 2½ | ⅜ | 1 |

REMA TIP TOP/North America, Inc.

300 Tice Boulevard, Suite 250 • Woodcliff Lake, NJ 07677 • Phone 800.225.REMA (7362) • 201.768.8100 → www.rematiptop.com