

# ELECTRIC DUPLEX



3112DL

## Two Stage Electric Duplex

Model	Part No.	HP	Voltage/ Ph.	CFM @ 100psi	CFM @ 175psi	Tank (Gal.)	Max Pressure (PSI)	Ship Wt.* (Lbs)	Dimensions L x W x H
3112D	8090254734	2 x 5	230/1	37.2	33.2	120H	175	778	77 x 27 x 56
3312D	8090254742	2 x 5	230/3	37.2	33.2	120H	175	778	77 x 27 x 56
3312D4	8090254759	2 x 5	460/3	37.2	33.2	120H	175	778	77 x 27 x 56
3112DL	8090254767	2 x 7.5	230/1	50.5	44.6	120H	175	886	77 x 27 x 56
3312DL	8090254770	2 x 7.5	230/3	50.5	44.6	120H	175	886	77 x 27 x 56
3312DL4	8090254773	2 x 7.5	460/3	50.5	44.6	120H	175	886	77 x 27 x 56

## Iron Series Duplex

4112D	8090254783	2 x 5	230/1	36	32	120H	175	1023	77 x 27 x 56
4312D	8090254791	2 x 5	230/3	36	32	120H	175	1023	77 x 27 x 56
4312D4	8090254809	2 x 5	460/3	36	32	120H	175	1023	77 x 27 x 56
4112DL	8090254817	2 x 7.5	230/1	46	42	120H	175	1131	77 x 27 x 56
4312DL	8090254825	2 x 7.5	230/3	46	42	120H	175	1131	77 x 27 x 56
4312DL4	8090254833	2 x 7.5	460/3	46	42	120H	175	1131	77 x 27 x 56
6312D	8090254841	2 x 10	230/3	70	64	120H	175	1395	81 x 27 x 52
6312D4	8090254858	2 x 10	460/3	70	64	120H	175	1395	81 x 27 x 52
6320D	8090254866	2 x 10	230/3	70	64	200H	175	1525	85 x 27 x 52
6320D4	8090254874	2 x 10	460/3	70	64	200H	175	1525	85 x 27 x 52

Specifications Subject to Change without Notice

\*Shipping weights may vary

## STANDARD FEATURES:

Alternating Control Panel  
 Mounted/Wired Magnetic Starters  
 Dual Magnetic Starter Controls  
 Up to 50.5 CFM on Single Phase  
 Up to 70 CFM on Three Phase  
 ASME Tank and Safety Valves

