



Reliable lift systems for independent repair shops, car dealerships, bodyshops, home enthusiasts, and heavy-duty truck facilities.

## I-12 PR

LIGHT DUTY TWO POST LIFT 12,000 lbs. Capacity

## **FEATURES:**

Symmetrical column design

Versatile 3-stage front and rear arms

Four height configuration models for most ceiling heights

Adjustable width options

- Cylinder rod concealed inside carriage
- · Overhead cable equalization
- · Single point lock release
- Spring operated arm restraints
- · Includes adapter storage bracket
- Durable powder-coated finish

SPECIFICATIONS

with 5" Extension

Adjustable Overall

Height Options

Overall Width

Overhead Switch

Height Options

Min/Max Adapter Height

Width inside

Voltage/Amps

Motor/Phase

Ceiling Height required

Drive through clearance

Front Reach (Min/Max)

Rear Reach (Min/Max)

Capacity Maximum Rise I12N300BL/RD 12,000 lbs. (5443kg)

80-3/4" (2051mm)

**I12N302** 154" (3912mm)

I12N303 143" (3632mm)

I12N303 137-1/8" (3483mm

27-3/4" / 59" (705mm/1460mm) 27-3/4" / 59" (705mm/1460mm)

4-3/4" (121mm) w/o extension

9-3/4" (248mm) w/5" extension

120-7/8" (3070mm) Adjustable

114-7/8" (2918mm) Standard

1ph/2HP/50Hz; 1ph/2HP/60Hz

208V/230V, 17 amps

168" (4267mm)

112N300 166" (4216mm) Standard

I12N301 178" (4521mm) Max. Height

140" (3556mm) or optional 146" (3708mm)

112N300 160-1/8" (4067mm) Standard

I12N301 172-1/8" (4524mm) Extended I12N302 148-1/8" (3762mm)

108-3/4" (2762mm) or optional 102-3/4" (2610mm)

ALI certified

**INCLUDES LOW-PROFILE DROP-IN ADAPTERS AND (4 each) ADAPTER EXTENSIONS** AT 1.75", 3.5" and 5"





www.forwardlift.com 📑 💿 👽 🕟

FWD I12N300BL

996 Industrial Drive Madison, IN 47250

Phone: 800.423.1722 Fax: 812.273.7329

