

GENERAL PURPOSE TIRE CHANGER

monty<sup>®</sup>

TIRE CHANGING SYSTEMS

1575



**HOFMANN**<sup>®</sup> 

1575



## MONTY 1575 TIRE CHANGERS

The monty® 1575 is ideal for shops looking for great value without sacrificing productivity. It includes wheel protectors so even the most expensive wheels can be changed without additional expense and fear of cosmetic damage. The monty 1575 can also be upgraded by adding Hofmann's patented EasyMont Pro, aiding in single-operator mounting/demount of extra-stiff, low-profile, high-performance and fun-flat tires.

### ACCOMMODATES LARGE WHEEL & TIRE ASSEMBLIES

- Allowing for a tire diameter of 40" (101.6 cm) and outer-wheel diameters of 21" (53 cm), the month 1575 can handle wheel and tire assemblies found on cars and light trucks

### DUAL WHEEL CLAMPING CYLINDERS

- Dual pneumatic clamping cylinders control all four clamping jaws, eliminating damage to wheels due to slippage

### ADJUSTABLE FOUR-JAW CLAMPING CHUCK

- Self-centering jaw clamps wheels from either 26" inner or 24" (61 cm) outer diameter

### POWERFUL TWO-STAGE BEAD BREAKER

- 6,000 lbs (2,722 kg) of power at the bead shovel and a range of up to 14" (35.6 cm) wide. The two-stage pneumatic cylinder provides precise power and can be toggled with the foot pedal as needed. Both the stiffest and the softest sidewalls are a snap. No damage to tires while loosening the beads

### POWERFUL TIRE INFLATION SYSTEM

- Powerful air blast operated by the foot pedal. Each movable jaw is precisely set to the exact position under the wheel to seal the tire bead

### UPGRADE WITH OPTIONAL EASYMONT PRO

- EasyMont Pro features a three-piece design with a top roller, pressing foot and lifting disc. Each piece provides a specialized function that assists a single operator in mounting/demounting low-profiles and high performance tires

### TECHNICAL SPECIFICATIONS

Overall wheel clamping diameter	10" - 26" (25 - 66 cm)
Inner wheel clamping diameter	12" - 26" (30 - 66 cm)
Outer wheel clamping diameter	10" - 24" (25 - 61 cm)
Bead breaker range	3" - 13" (7.6 - 33 cm)
Bead loosening power	6,000 lbs (2,722 kg)
Maximum wheel width	13" (33 cm)
Max outer tire diameter	40" (101.6 cm)
Shipping weight	550 lbs (249.5 kg)
Power requirements	120V 1Ph 60Hz

### DRIVE MOTOR OPTIONS

Electric (standard)	1HP
---------------------	-----

### OPTIONAL ACCESSORIES

EasyMont Pro bead assist device	EAA0329G36B
Automotive adapters	EAA0351G93A
ATV adapters	EAA0351G92A
Quick change bead head kit	EAA0304G66A
Composite mount/demount head	EAA0247G20A
Protective cover for tire lever	EAA0247G04A
Outside clamping jaw protectors	EAA0304G20A
Protective cover for bead breaker	EAA0304G15A
Rim protector (3)	EAA0304G52A
Mount/demount protective insert	EAA0247G15A
Replacement composite head	EAM0304G52A
Wave tire tool	EAA0304G14A
Magic bead pusher	EAA0377G23A
Round bar with roller attachment	EAA0332G32A
Hex bar with roller attachment	EAA0329G92A
Bead breaker disc	EAA0304G43A
Bead clamp for performance wheels	EAA0247G70A
Bead clamp for run-flat tires	EAA0247G11A
Premium tire paste	8-03229A

For more information regarding the monty® 1575, call 800.251.4500 (US) or 800.267.2185 (Canada) [www.hofmann-equipment.com](http://www.hofmann-equipment.com)

Hofmann is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet piece may change without notice. ©2020 Snap-on Incorporated. Hofmann is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders. 09/2020 SS3272B