

# R980DP

## Swing-Arm Tire Changer

with Dual Assist Tower / 30" Clamping Capacity

SKU# 5140174 - 220V

SKU# 5140176 - 110V (L Model)

### The Ultimate Swing-Arm Tire Changer

When it comes to tire and wheel service, the R980DP and R980DP-L stand out as powerhouse machines, designed for shops that refuse to compromise. Offering identical features and performance capabilities, the key distinction between these two models is the voltage: the R980DP operates on 220 volts and provides seamless integration into high-demand environments, while the R980DP-L is compatible with standard 110-volt outlets, making the R980DP-L ideal for smaller shops, temporary setups, or locations prioritizing cost-effective installation.

The R980DP isn't just built for everyday jobs—it's engineered to handle the big ones, too. With its robust design and adjustable RimGuard™ clamps, this tire changer easily tackles wheels up to 30 inches in diameter. Whether it's oversized truck tires, custom alloys, or large-diameter performance wheels, the R980DP delivers precision and power in equal measure. The dual assist towers and high-torque turntable ensure smooth, secure operation, even with heavy or awkwardly sized tires, giving your shop the capability to handle high-demand jobs without breaking a sweat. It's the ultimate solution for shops that never back down from a challenge.

### Features

- Electric Turntable
- TurboBlast Bead Seating
- Rim Clamping System
- Dual Pneumatic Assist Arms
- Bead Roller
- Multi-Assist Tool
- Tool Holder
- Water Filter
- Oil / Lubricator
- Air regulator
- Brush
- Alloy-Steel Mount / Demount Head
- Plastic-Polymer Mount / Demount Head
- Inflation Pressure Regulator/Limiter
- Inflation Gauge w/ integrated Air Dump Valve



### Specifications

<b>Motor</b>	208-240 VAC, 50-60 HZ (SKU 5140174) 110 VAC, 50-60 HZ (SKU 5140176)
<b>Drive System Type</b>	Electric / Air
<b>Internal Rim Clamping</b>	9 - 30" (254 - 762 mm)
<b>External Rim Clamping</b>	9 - 26" (229 - 660 mm)
<b>Turntable Tire Width Capacity (Mounting)</b>	4 - 15" (102 - 381 mm)
<b>Bead Breaker Tire Width Capacity (Demounting)</b>	1.5 - 13" (38 - 330 mm)
<b>Max. Tire Diameter</b>	50" (1,270 mm)
<b>Product Dimensions</b>	47" L x 60" W x 82" H (1200 mm x 1530 mm x 2090 mm)



# Ranger®