

# SPOA7-MP

## ADJUSTABLE LOW DRIVE-OVER PAD LIFTS

**SPOT VEHICLES QUICKLY,  
EASILY, AND ACCURATELY  
-PERFECT FOR A QUICK  
LUBE BAY!**

### IMPROVE YOUR REACH!

Lower profile  
moveable pad  
adjusts to fit most  
unibody vehicles.

#### Minimum Pad Measurements:

Minimum distance between pads: 39 9/16"  
Overall retracted pad length: 70 13/16"

#### Maximum Pad Measurements:

Maximum distance between pads: 55 9/16"  
Overall extended pad length: 86 13/16"

#### Minimum Pad Height: 2 5/8"

Low drive-over clearance minimizes  
vehicle spotting time



#### Rubber spacer blocks provide clearance

Includes four (4) each  
1.5" and 3" blocks



Model shown:  
**SPOA7N17X0BL**

### CUSTOMIZE TO FIT THE NEEDS OF YOUR SHOP!

#### CHOOSE FROM FOUR OPTIONAL WIDTH INSTALLATION OPTIONS:

Add up to 14 5/8" of additional  
drive-thru for wide vehicles.

#### FEATURES:

- Extended height models available
- Available with SHOCKWAVE™ power
- Original "Double S" column
- All Gold Certified

#### SPECIFICATIONS

| STANDARD POWER<br>BL = Blue / RD = Red |                           | SPOA7N17X0BL<br>SPOA7N17X0RD       |
|----------------------------------------|---------------------------|------------------------------------|
| SHOCKWAVE<br>EQUIPPED                  |                           | SPOA7U17X5BL<br>SPOA7U17X5RD       |
| Rise*                                  | STANDAR<br>With SHOCKWAVE | 71" to 74"<br>74" to 77"           |
| Overall Height                         | With SHOCKWAVE            | 11' 11 1/2"<br>12' 5 1/2"          |
| Overall Width                          |                           | 11' 5 1/4" - 12' 7 7/8"            |
| Drive-thru                             |                           | 79 3/8" - 94"                      |
| Inside Columns                         |                           | 107 1/8" - 121 3/4"                |
| Min Bay Size                           |                           | 12' X 24'                          |
| Ceiling Height Min                     | With SHOCKWAVE            | 12'<br>12' 6"                      |
| Motor / Voltage                        | With SHOCKWAVE            | 2 HP, 208-230V<br>5 HP / 110V      |
| Time of Rise / Descent                 | With SHOCKWAVE**          | 45 / 40 seconds<br>25 / 19 seconds |

\*Rise measures lowest and highest position of the  
supplied adapters from floor to full cylinder stroke

\*\*Times vary depending on vehicle weight

Heights and widths reflect standard settings



PART OF VSG a DOVER company

#### ROTARY SOLUTIONS

To learn more about all of our automotive service and repair solutions or to contact your local distributor, visit us at [www.RotarySolutions.com](http://www.RotarySolutions.com) today.

**Need assistance or have questions? We're here to help:** 800.445.5438

Sales: [insidesales@rotarysolutions.com](mailto:insidesales@rotarysolutions.com) / Technical Support: [LD-techsupport@rotarysolutions.com](mailto:LD-techsupport@rotarysolutions.com)

#### ROTARY SOLUTIONS™

2700 Lanier Drive | Madison, IN 47250, U.S.A.

Lit# Rotary.SPOA7MP.Cutsheet.07.01.2026

©2026 VEHICLE SERVICE GROUP™

All Rights Reserved. Unless otherwise indicated, ROTARY SOLUTIONS™, VEHICLE SERVICE GROUP™, DOVER® and all other trademarks are property of Dover Corporation and its affiliates.

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability.



ROTARY  
SOLUTIONS

SERVING THE SHOP™ SINCE 1925