

# Safety Data Sheet

Issue Date: 07/09/2015

Revision Date: 07/09/2015

SDS Number: 10-CVC-01  
Version: 1

## Section 1: Identification

### Product Identifier

SV8 SV32

Product Name: Chemical Vulcanizing Cement Flammable  
Chemical Vulcanizing Cement Fast Dry Flammable

Catalog No: 1-700, 1-701, 1-702, 1-703, 1-704, 2-700, 2-701, 2-702, 2-703, 2-704, 4-700, 4-701, 4-702, 4-703, 4-704, 1-644, 1-645, 1-646, 1-647, 1-648, 2-644, 2-645, 2-646, 2-647, 2-648, 4-644, 4-645, 4-646, 4-647, 4-648

### Other means of Identification

SDS #: 10-CVC-01  
UN/ID No: UN1133

### Recommended use of Chemical & restriction on use

Recommended Use: Rubber adhesive  
Restriction use: No further relevant information available

### Details of the supplier of the safety data sheet

Manufacturer/Supplier:  
Plant-1  
600 N Magnolia Ave  
Luling, TX 78648  
Phone: (830) 875-5539  
Fax: (830) 875-5562

### Emergency Telephone Number

INFOTRAC Company Phone Number: +1 (352) 323-3500  
EMERGENCY Telephone (24hr): INFOTRAC +1 (352) 323-3500 (International)  
1-800-535-5053 (North America)

## Section 2: Hazards Identification


### Classification of the substance or mixture

OSHA/HCS status: This material is considered hazardous by the OSHA GHS Hazard Communication Standard (29 CFR 1910.1200).

Classifications:	Flam. Liq.	Category 2	H225 Highly flammable liquid and vapour.
	Asp. Tox.	Category 1	H304 May be fatal if swallowed and enters airways.
	Skin Irrit.	Category 2	H315 Causes skin irritation.
	STOT SE	Category 3	H336 May cause drowsiness or dizziness.
	Aquatic Acute	Category 1	H400 Very toxic to aquatic life.
	Aquatic Chronic	Category 1	H410 Very toxic to aquatic life with long lasting effects.

**GHS Label Elements**

## Pictograms:



Appearance: Colourless liquid

Physical State: Liquid

Odor: Petrollic

Signal Word: DANGER

## Hazards Statements:

H225 Highly flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.  
 H336 May cause drowsiness or dizziness.  
 H410 Very toxic to aquatic life with long lasting effects.

## Precautionary Statements - Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces - NO Smoking.  
 P233 Keep container tightly closed.  
 P240 Ground / bond container and receiving equipment.  
 P241 Use explosion-proof electrical, ventilating, and lighting equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P261 Avoid breathing mist / vapours.  
 P264 Wash skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves and eye / face protection.

## Precautionary Statements - Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
 P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse skin with water/shower  
 P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
 P321 Specific treatment(see supplemental first aid instructions on this label).  
 P331 Do NOT induce vomiting.  
 P332+P313 If skin irritation occurs: Get medical advice/attention.  
 P362 Take off contaminated clothing and was before reuse.  
 P370 + P378 In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO2) for extinction.  
 P391 Collect spillage.

**Precautionary Statements - Storage:**

P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P403+P235 Store in a well-ventilated place. Keep cool.  
 P405 Store locked up.

**Precautionary Statements - Disposal:**

P501 Dispose of contents/container to an approved waste disposal plant.

**Hazards not otherwise classified (HNOC)**

Other Hazards: Harmful to aquatic life with long lasting effects.

**Section 3: Composition/Information on Ingredients****Substances**

Chemical Names: HEPTANE; n-Heptane; Heptan; Heptyl hydride; 142-82-5; Dipropyl methane  
 Formula: C7H16  
 Molecular Weight: 100.20g/mol  
 EC-No: 205-563-8  
 Index: 601-008-00-2

Components	CAS No	Weight-%
Heptane	142-82-5	80% - 95%
Trichloroethylene	79-01-6	5% - 15%
Zinc Dibutyldithiocarbamate	136-23-2	0% - 2%

**Section 4: First-Aid Measures****First Aid Measures**

**Eye Contact:** Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

**Skin Contact:** Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

**Inhalation Contact:** If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. Get immediate medical attention.

**Ingestion Contact:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If victim is conscious: Rinse mouth out with plenty of water. Let victim drink water as much as possible in small sips. Get immediate medical attention.

### Most Important Symptoms and Effects

**Symptoms:** Causes skin and eye irritation. Possible symptoms are irritation of the mucous membranes, dry cough and respiratory difficulty. Symptoms may include dizziness, headache, nausea and loss of coordination. Suitable first-aid treatment should be immediately available. Seek medical advice before using product. May result in pulmonary oedema.

### Most Important Symptoms and Effects

**Notes to Physician:** Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to high concentrations of hydrocarbon solvents. (e.g., in enclosed spaces or with deliberate use.) The use of other drugs with less arrhythmogenic potential should be considered. If sympathomimetic drugs are administered, observe for the development of cardiac arrhythmias.

## **Section 5: Fire-Fighting Measures**

### Suitable Extinguishing Media

**Suitable Extinguishing:** Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

**Unsuitable Extinguishing:** Do not use a solid water stream. Flash back possible over considerable distances.

### Specific Hazards Arising from the Chemical

\* Flammable, container may explode when heated. Flash back possible over considerable distances.

**Hazardous Combustion Products:** Carbon dioxide and Carbon monoxide.

**Sensitivity to Static Discharge:** No further relevant information available

### Protective equipment and precautions for firefighters

**Advice for firefighters:** Wear self contained breathing apparatus for fire fighting if necessary. In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray to cool unopened containers.

## **Section 6: Accidental Release Measures**

### Personal precautions, protective equipment and emergency procedures

**Personal Precautions:** Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation.

**For Emergency Responders:** Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

**Precautions for Environments**

**Environmental Precautions:** Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

**Methods and materials for containment and cleaning up**

**Methods for Containment:** Contain spillage and ventilate area. Keep away from ignition sources (including static discharges). Evacuate area. Prevent evaporation by covering with foam.

**Methods for Clean-up:** Absorb excess liquid spillage on inorganic adsorbent material such as fine sand, brick dust etc. Place spent adsorbent in sealed packages and contact specialist waste disposal contractor.

**Section 7: Handling and Storage****Precautions for safe handling**

**Advice on Safe Handling:** Handle in accordance with good industrial hygiene and safety practices. Do not handle until all safety precautions have been read and understood. For precautions see section 2.2. Use personal protection recommended in Section 8. Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions:** Store under inert gas. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Avoid heat, flames, sparks and other sources of ignition. Wear splash resistant goggles, chemical resistant clothing and gloves, and adequate respiratory mask.

**Specific end use(s)**

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

**Section 8: Exposure Controls/Personal Protection****Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
(n-) Heptane 142-92-5	400 ppm (1,640 mg/m <sup>3</sup> ) TWA 500 ppm (2,050 mg/m <sup>3</sup> ) STEL	400 ppm (1,600 mg/m <sup>3</sup> ) TWA 500 ppm (2,000 mg/m <sup>3</sup> ) STEL	85 ppm (350 mg/m <sup>3</sup> ) TWA 440 ppm (1,800 mg/m <sup>3</sup> ) Ceiling (15 minutes)
Trichloroethylene 79-01-5	50 ppm (269 mg/m <sup>3</sup> ) TWA 100 ppm (537 mg/m <sup>3</sup> ) STEL	100 ppm (537 mg/m <sup>3</sup> ) TWA 200 ppm (1074 mg/m <sup>3</sup> ) ceiling (5 minutes)	25 ppm TWA 10 hour(s) 2 ppm ceiling 60 minute(s)

**Legend:**

ACGIH - American Conference of Governmental Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH - The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

### Appropriate engineering controls

**Engineering Controls:** Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment. Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

### Individual protection measures, such as personal protective equipment

**Eye/Face Protection:** Wear splash resistant goggles or safety glasses that have been tested and approved under government standards.

**Skin and Body Protection:** Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

**Respiratory Protection:** Keep self contained breathing apparatus readily available for emergency use. If respiratory protection is needed, use only protection authorized in the U.S. Federal OSHA Standards(29CFR 1910.134), applicable U.S. State regulations, or Canadian CSA Standards 29.14-93 and applicable standards of Canadian Provinces. Oxygen levels below pressure/demand SCBA or a full facepiece, supplied air respirator with auxiliary self-contained air supply is required under OSHA's Respiratory Protection Standards (1910.134-1996).

**General Hygiene Considerations:** Handle in accordance with good industrial hygiene and safety procedures. Refer to local regulations for restriction of waste disposal.

## **Section 9: Physical and Chemical Properties**

### Information on basic physical and chemical properties

**Physical State:** Liquid

**Appearance:** High viscosity liquid, cloudy

**Color:** Clear, Colorless liquid

**Odor:** Petrolic

**Odor Threshold:** Not determined

pH:	Not determined
Melting Point/Freezing Point:	-91.0 to -90.1 °C; -131.7 to -130.3 °F; 182.2 to 183.0 K
Boiling Point/Boiling Range:	98.1 to 98.7 °C; 208.5 to 209.6 °F; 371.2 to 371.8 K
Flash Point:	-4.0 °C (24.8 °F; 269.1 K) - closed up
Evaporation Rate:	Not determined
Flammability (solid, gas):	Not determined
Upper Flammability Limits:	7% (V)
Lower Flammability Limits:	1.1% (V)
Vapor Pressure:	110.7 hPa (83.0 mmHg) at 37.7 °C (99.9 °F) 53.3 hPa (40.0 mmHg) at 20.0 °C (68.0 °F)
Vapor Density:	3.30 (Air=1)
Specific Gravity:	0.684 g/mL at 25 °C (77 °F)
Solubility in other Solvents:	insoluble
Partition Coefficient:	log Pow: > 3.000
Autoignition Temperature:	223.0 °C (433.4 °F; 496.1 K)
Decomposition Temperature:	Not determined
Viscosity:	Not determined
Explosive Properties:	Not determined
Oxidizing Properties:	Not determined

### Other safety information

Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

## **Section 10: Stability and Reactivity**

### Reactivity

Not reactive under normal conditions.

### Chemical Stability

Stable under recommended storage conditions.

**Possibility of Hazardous Reaction**

Vapors may form explosive mixture with air

**Conditions to Avoid**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

**Incompatible Materials**

Strong oxidizing agents

**Hazardous Decomposition Products**

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition: Carbon dioxide and Carbon monoxide.

**Section 11: Toxicological Information****Information on likely routes of Exposure**

Eye Contact: Cause severe eye irritation  
 Skin Contact: Cause skin irritation  
 Inhalation: May be harmful if inhaled,  
 Ingestion: May be harmful if swallowed

**Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Heptane (n-) 142-82-5	> 5000 mg/kg (rat)	-	103 mg/l (rat) 4hrs

symptoms: Please see section 4 of this SDS for symptom information.

Carcinogenicity: This product contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

Reproductive Toxicity: No data available

STOT-single exposure: May cause drowsiness or dizziness.

STOT-repeated exposure: May cause skin dryness or cracking.  
May result in skin and/or respiratory sensitivity.

Aspiration Hazard: May be fatal if swallowed and enters airways.



## Section 12: Ecological Information

### Ecotoxicity

**Toxicity to fish:**

LC50 - Carassius auratus (goldfish) - 4 mg/l - 24.0 h  
LC50 - Tilapia mossambica - 375 mg/l - 96.0 h

**Toxicity to daphnia and other aquatic invertebrates:**

EC50 - Daphnia magna (Water flea) - 1.50 mg/l - 48 h

### Persistence and degradability

Ratio BOD/TnBOD 3.5 %

### Bioaccumulative potential

Indication of bioaccumulation.

### Mobility in soil

no data available

### Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

### Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life with long lasting effects.

Do not empty into drains. Avoid release to the environment.

## Section 13: Disposal Considerations

### Waste Treatment Methods

**Product:** Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state, and local requirements.

**Contaminated Packaging:** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Section 14: Transport Information****DOT**

UN/ID No: UN1133  
Proper Shipping Name: Rubber Adhesive (Heptanes (n-))  
Hazard Class: 3  
Packing Group: II  
Environmental Hazards: No  
Special Provisions: Based on packaging size, product may be eligible for limited quantity exceptions or reclassified as ORM-D.

**IATA**

UN/ID No: UN1133  
Proper Shipping Name: Rubber Adhesive (Heptanes (n-))  
Hazard Class: 3  
Packing Group: II  
Environmental Hazards: No  
Special Provisions: Based on packaging size, product may be eligible for limited quantity exceptions or reclassified as ORM-D.

**IMDG**

UN/ID No: UN1133  
Proper Shipping Name: Rubber Adhesive (Heptanes (n-))  
Hazard Class: 3  
Packing Group: II  
EMS: F-E, S-D  
Environmental Hazards: Yes (Heptane (n-))  
Special Provisions: Based on packaging size, product may be eligible for limited quantity exceptions or reclassified as ORM-D

**Special Precautions**

Transport within user's premises: Always transport in closed containers that are upright and secure. Ensure that personnel transporting the product know what to do in the event of an accident or spillage.

Transport in bulk: According to Annex II of MARPOL 73/78 and the IBC Code.

## Section 15: Regulatory Information

### U.S. Federal Regulations

SARA 311/312 Hazards:	Fire hazard
SARA 302 Reportable Quantity:	This material does not contain any components with a SARA 302 RQ.
SARA 302 Threshold Planning Quantity:	SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA 304 Reportable Quantity:	This material does not contain any components with a section 304 EHS RQ.
SARA 313 Ingredients:	SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
CERCLA Component Analysis:	None of this products components are listed under CERCLA (40 CFR 302.4).
TSCA Component Analysis:	Components of this product have been checked against the nonconfidential TSCA inventory by CAS Registry Number. Components not identified on this nonconfidential inventory are either exempt from listing (i.e. polymers, hydrates) or are listed on the confidential inventory as declared by the supplier. Component Analysis - Inventory
CAS # TSCA CAN EEC:	Heptane (n-) 142-82-5, Yes DSL EINECS

### Right-to-Know

Massachusetts Right to Know Components:	Heptane (n-) 142-82-5 Trichloroethylene 79-01-6
Pennsylvania Right To Know Components:	Heptane (n-) 142-82-5 Trichloroethylene 79-01-6
New Jersey Right To Know Components:	Heptane (n-) 142-82-5 Trichloroethylene 79-01-6
California Prop. 65 Components:	This product does contain known to State of California to cause cancer, birth defects, or any other reproductive harm.

### Canadian Regulations

WHMIS Classification:	Class B-2, Flammable & Combustible Materials Class D-2A & D-2B: Material Causing other Toxic Effects
WHMIS IDL Component Analysis:	The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List.
CAS # Minimum Concentration:	Heptane (n-) 142-82-5 = 1% (Eng. Item 806, FR. Item 940)

**Section 16: Other Information****NFPA Classification**

Health Hazard: 1  
Fire Hazard: 3  
Reactivity Hazard: 0

**HMS Classification**

Health Hazard: 1  
Fire Hazard: 3  
Reactivity Hazard: 0

**Other Information**

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Revision Number:

Revision Date:

SDS Prepared by:

**DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES**

The information in this document is believed to be correct as of the date issued. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM HAZARDS RELATED TO ITS USE. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of his use thereof.