

14K SCISSOR ALIGNMENT

SX14

Easy to operate and load, this 14,000 lbs. lift comes standard with productivity upgrades like LED lighting, pneumatic single-point locking rear slip plates, and a photocell to ensure runway synchronization. Flush- and Surface-mount options are available.

REQUIREMENTS

- 12' MINIMUM**
- 14' RECOMMENDED**
- 28' RECOMMENDED**
- 208-230V, 1PH, 30A**
- 90-120 PSI**



| MODEL NUMBER | SX14 | SX14-FM | SX14-ER |
|------------------------------------|-------------------------------------|-------------|----------------|
| Description | Standard | Flush Mount | Extended Ramps |
| Lifting Capacity | 14,000 lbs. | | |
| Overall Width (A) | 91 1/4" | | |
| Overall Length (B) | 265" | 219" | 283" |
| Width Between Platforms (C) | 40" | | |
| Platform Width (D) | 25 1/2" | | |
| Distance to Controls (E) | 156" | | |
| Rise Height (F) | 77" | 66 1/2" | 77" |
| Lowered Height (G) | 10 1/2" | NA | 10 1/2" |
| Max. Wheelbase (H) | 183" | | |
| Wheel Alignment Max. (J) | 176" | | |
| Wheel Alignment Min. (K) | 70 3/4" | | |
| Platform Length | NA | | |
| Ramp Length | 62 3/4" | | 80 3/4" |
| Standard Motor/Voltage | 3HP, 208-240v, 60Hz, 1Ph | | |
| Rise Time | 75s | | |
| Max. Load per Platform | 7,000 lbs. | | |
| ALI® Certified | <input checked="" type="checkbox"/> | | |

