

# TWO STAGE ELECTRIC 5 HP AND 7.5 HP

Two Stage Electric Simplex									
Model	Part No.	HP	Voltage/ Ph.	CFM @ 100psi	CFM @ 175psi	Tank (Gal.)	Max Pressure (PSI)	Ship Wt.* (Lbs)	Dimensions W x L x H
<b>5HP Single Phase Compressors - These Units Do Not Require a Magnetic Starter</b>									
4916V	8090303119	5	230/1	15.4	14.7	60V	165	327	28 x 23 x 70
4918VN	8090303168	5	230/1	15.4	14.6	80V	175	381	27 x 31 x 69
318VN	8090250017	5	230/1	18.6	16.6	80V	175	428	39 x 24 x 77
318HN	8090250012	5	230/1	18.6	16.6	80H	175	468	71 x 24 x 49
<b>5HP Compressors - These Units Include a Mounted/Wired Magnetic Starter</b>									
318V	8090250369	5	230/1	18.6	16.6	80V	175	457	39 x 24 x 77
318H	8090250008	5	230/1	18.6	16.6	80H	175	491	71 x 24 x 49
338V	8090250026	5	230/3	18.6	16.6	80V	175	457	39 x 24 x 77
338V4	8090252837	5	460/3	18.6	16.6	80V	175	457	39 x 24 x 77
338H	8090250022	5	230/3	18.6	16.6	80H	175	471	71 x 24 x 49
338H4	8090252845	5	460/3	18.6	16.6	80H	175	471	71 x 24 x 49
<b>7.5HP Compressors - These Units Include a Mounted/Wired Magnetic Starter</b>									
318VL	8090250015	7.5	230/1	25.3	22.3	80V	175	479	39 x 24 x 77
318HE	8090250012	7.5	230/1	25.3	22.3	80H	175	538	71 x 24 x 49
338VL	8090250028	7.5	230/3	25.3	22.3	80V	175	467	39 x 24 x 77
338VL4	8090250034	7.5	460/3	25.3	22.3	80V	175	467	39 x 24 x 77
338HE	8090250024	7.5	230/3	25.3	22.3	80H	175	481	71 x 24 x 49
338HL4	8090250031	7.5	460/3	25.3	22.3	80H	175	481	71 x 24 x 49
<b>5HP ELITE Compressors - These Units Include a Mounted/Wired Magnetic Starter/Low Oil Switch &amp; Auto Drain</b>									
318VLE	8090250014	5	230/1	18.6	16.6	80V	175	467	39 x 24 x 77
318HE	8090250009	5	230/1	18.6	16.6	80H	175	501	71 x 24 x 49
338VE	8090250027	5	230/3	18.6	16.6	80V	175	453	39 x 24 x 77
338VE4	8090250033	5	460/3	18.6	16.6	80V	175	453	39 x 24 x 77
338HE	8090250023	5	230/3	18.6	16.6	80H	175	481	71 x 24 x 49
338HE4	8090250030	5	460/3	18.6	16.6	80H	175	481	71 x 24 x 49
<b>7.5HP ELITE Compressors - These Units Include a Mounted/Wired Magnetic Starter/Low Oil Switch &amp; Auto Drain</b>									
318VLE	8090250016	7.5	230/1	25.3	22.3	80V	175	477	39 x 24 x 77
318HLE	8090250011	7.5	230/1	25.3	22.3	80H	175	548	71 x 24 x 49
338VLE	8090250029	7.5	230/3	25.3	22.3	80V	175	477	39 x 24 x 77
338VLE4	8090250035	7.5	460/3	25.3	22.3	80V	175	477	39 x 24 x 77
338HLE	8090250025	7.5	230/3	25.3	22.3	80H	175	491	71 x 24 x 49
338HLE4	8090250032	7.5	460/3	25.3	22.3	80H	175	491	71 x 24 x 49

Specifications Subject to Change without Notice

\*Shipping weights may vary

## STANDARD FEATURES:

Start-Stop Pressure Switch Controls  
 Cast Iron Cylinders  
 Aluminum Heads and Aftercoolers  
 for Superior Cooling  
 ASME Tank and Safety Valves  
 100% Factory Tested

**2 FULL  
YEAR  
WARRANTY**

